


FEATURES

- Wire restraint electrode safely secures leadwires preventing artifact associated with movement
- Specially designed electrode shape helps ease of correct placement with curved top
- Stainless steel snap minimizes the amount of noise artifact due to lower incidence of corrosion compared to nickel-plated brass used by competitors



SINGLE USE PACKS
Packaged in no-waste quantities



RESEALABLE BULK POUCH
Contains 30 or more electrodes



CASE
FDA / GS1 Compliant Labels





PerformancePlus™ Electrodes

Leadlocking™ Electrodes by Vermed

Don't let wires get in the way. Leadlocking™ electrodes save time and money eliminating the need to tape down wires or replace displaced electrodes. Ensure patient comfort and accuracy by preventing motion artifact.

A10072 - 2.25" x 1.5" / 57.15mm x 38.1mm - LEADLOCKING™ ELECTRODE

Product #	Per Strip	Per Pouch	Per Box	Per Case	Wet Gel	Duration of Use
A10072-1-60	1	60	n/a	600		 24 Hours
A1007-10	10	10	n/a	900		
A10072-1-30	1	30	n/a	900		
A10072-3	3	3	n/a	600		
A10072-5	5	5	n/a	550		
A10072-7	7	7	n/a	700		

ROUNDED TOP

Rounded top designed for ease of placement and allows perspiration to move off of the electrode preventing pooling. Aggressive adhesive stays in place during the vigorous movement that occurs during a stress test.

SLIT

Slit allows bottom tab of electrode to be placed over the leadwire

NO NEED FOR TAPE

Bottom tab of the electrode is placed on top of the leadwire removing the need to use tape



A10072
Foam | Solid Gel

GROOVED HOLE

Grooved hole allows the leadwire to pass through the electrode and attach to standard snap